


PLATINUM HT-SA Underlayment

PLATINUM HT-SA Underlayment



FEATURES:

- Self-Adhering without Heat or Special Adhesives
- Installation Temperature: 40°F (4.4°C) and above
- Seals around fasteners
- UV Resistant film provides up to 6 months exposure rating
- Synthetic construction to inhibit mold growth
- Superior deck adhesion and lap strength
- Slip-resistant walking surface
- Ideal for use under metal roofing
- Meets and exceeds ASTM D1970



PLATINUM HT-SA Roll Specifications

Length per Roll	67 ft. (20.4 m)
Width per Roll	36" (914 mm)
Weight per Roll	40 lbs (18 kg)
Roll Size	2 Sq (18.6 m ²)
Rolls per Pallet (42" x 42")	25
Pallet Weight	1,000 lbs (454 kg)
Rolls per Truckload (40 Skids)	1000

Titanium® PSU-30 Technical Data

TEST & STANDARD		TYPICAL VALUES
Colour		Blue
Surface		GRIPSPOT® Enhanced Slip Resistance
Release Liner		Silicone treated, split-release
Weight per square		20 lbs (9 kg)
Nail Sealability	ASTM D1970	Pass
Permeability	ASTM E96	<0.035 perms
Minimum Thickness	ASTM D1970	41 mil (1.04 mm)
Tensile strength	ASTM D1970	MD 128 lb/in (50 kg) CD 107 lb/in (49 kg)
Thermal Stability	ASTM D1970	240°F (115°C) Pass
Low Temp. Flexibility	ASTM D1970	Pass
Tear Resistance	ASTM D1970	MD 70 lb/ft (32 kg) CD 60 lb/ft (27 kg)
Adhesion to Plywood	ASTM D903	4.0 lbs/in (0.9 kN/m)
UV Resistance		6 Months
Limited Warranty		Lifetime



PLATINUM HT-SA Underlayment

PLATINUM HT-SA Underlayment Specifications

